


Datasheet Conveyor Belt

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
2 LRWAF 907 NDP AS
- **Nitta Japan code:**



Construction: 2 plies polyester, rigid, antistatic

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	PVC	PVC	Whisper fabric	
Thickness:	0,7		-	mm (approx.)
Colour:	Black	Black	-	
Hardness:	85 Shore A		-	
Profile:	NDP		-	

Total thickness:	2,9		mm (approx.)
Weight:	2,8		kg/m² (approx.)
Max. width:	2000		mm
Belt support:	Sliderbed (Rollers), Flat		
Rating at 1% elongation:	10		N/mm
Advised pretension:	4 - 7		N/mm
Maximum allowable tension:	18		N/mm
Temperature range:	-10	to	+80 °C
Minimum pulley diameters:			
Flexing:	50		mm
Backflexing:	75		mm

Special approval: Not applicable

Applications: Jogging machines (treadmills)
General purpose conveying

Date of issue 22-07-2014-1