

Datasheet Conveyor Belt




**NITTA CORPORATION
OF HOLLAND**

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
2 LRWAF 901
- **Nitta Japan code:**



Construction: 2 plies polyester, rigid, antistatic

	TOP COVER	INNER LAYER	BOTTOM SIDE
Material:	Fabric	PVC	Whisper antistatic fabric
Thickness:	-	-	- mm (approx.)
Colour:	Black	Black	-
Hardness:	-	-	-
Profile:	-	-	-

Total thickness:	1,6	mm (approx.)
Weight:	1,7	kg/m ² (approx.)
Max. width:	3000	mm
Belt support:	Sliderbed (Rollers), Flat	

Rating at 1% elongation:	10	N/mm
Advised pretension:	4 - 7	N/mm
Maximum allowable tension:	18	N/mm
Temperature range:	-10 to +80	°C

Minimum pulley diameters:		
Flexing:	30	mm
Backflexing:	30	mm

Special approval: Not applicable

Applications: Accumulation belt
Internal transport, post offices and distribution centres
Luggage handling in airports and passenger terminals

Date of issue 17-12-2014-1

Your Partner In Belting Solutions

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nittacorporation.com