

Datasheet Conveyor Belt



**NITTA CORPORATION
OF HOLLAND**

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
2 RF 62
- **Nitta Japan code:**
GNC-16AOR



Construction: 2 plies polyester, rigid

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	PVC	PVC	Fabric	
Thickness:	2		-	mm (approx.)
Colour:	Green	Green	-	
Hardness:	65 Shore A		-	
Profile:	-		-	

Total thickness:	3,8		mm (approx.)
Weight:	4,5		kg/m ² (approx.)
Max. width:	3000		mm
Belt support:	Sliderbed (Rollers), Flat		
Rating at 1% elongation:	10		N/mm
Advised pretension:	4 - 7		N/mm
Maximum allowable tension:	20		N/mm
Temperature range:	-10	to +90	°C
Minimum pulley diameters:			
Flexing:	60		mm
Backflexing:	90		mm

Special approval: Not applicable

Applications: General purpose conveying
Oil and grease resistant

Date of issue 08-04-2014-1

Your Partner In Belting Solutions

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nittacorporation.com